

TacTest

Reference Transmitter Remote Video Terminals
2945 Commercial factory test version
2575 Ruggedised for service use



Features

- Sort range transmission on RVT frequencies (ROVER, STRIKEHAWK, etc)
- Built in camera
- Sealed to IP67
- Small, lightweight
- Integral Antenna
- 9-36vdc external power or standard radio battery
- Factory test version with built in battery

TACTEST is a self-contained unit for checking RVT operability either prior to a mission or during factory test.

In the field the **TACTEST** is used to check the RVT, which can then be used to check the aircraft pod.

The field version uses standard radio batteries (PR152 etc)

C Band Analogue Transmitter

4.4 GHz to 4.8 GHz (Factory set to order)

FM Demodulation

NTSC / RS-170 Video

Options available for:

L-Band (1.7 - 1.85GHz) or

S-Band (2.2 - 2.5GHz)

Dimensions

2945 180mm x 10mm x 5mm

2575 165mm x 50mm x 80mm

(Includes antenna and connectors)

Weight

2915 : 800g

2575: 1000g

Integral Camera

Lens: 3.6mm

Field of View: 82°

Light Sensitivity: 0.01 Lux F2.0

Battery

2945 Internal Battery with charger

2575 Clip on radio battery not included
(PR152, MBITR, PS etc)

External Power

9-36vdc

External Video Input